



**WET DIAMOND CORE DRILL**  
**DPWC**  
**SMALL DIAMETER CROWN**  
**BRICK / BLOCK & CONCRETE**



**CORE DRILL APPLICATIONS**

CLASS A ENGINEERING BRICKS	
FLINT AGGREGATE COMMON	
CLASS B ENGINEERING BRICKS	
LIGHTLY REINFORCED CONCRETE	
HEAVILY REINFORCED CONCRETE	
CONCRETE	
HARD YORK STONE	
LONDON BRICK	
GENERAL HOUSE BRICK	
HANDMADE BRICKS	
FACING BRICKS	
LIGHTWEIGHT CONCRETE BLOCK	
BREEZE BLOCK	
ABRASIVE SAND / GRITSTONE	

HIGHLY SUITED  
 SUITABLE WITH RESERVATIONS

**SIZES**

DPWC - 1/2" BSP (M) 200 mm Length
10DPWC
12DPWC

DPWC - 1/2" BSP (M) 350 mm Length
14DPWC
16DPWC
18DPWC
20DPWC
22DPWC
24DPWC
25DPWC
26DPWC
28DPWC
30DPWC
32DPWC

**EXCELLENT PERFORMANCE & OUTPUT**



**USE ME FOR**

All types of brick including class A & B engineering  
 All types of concrete including light & heavily reinforced  
 Stone such as Hard York  
 Occasional use in lightweight block and abrasive stone  
 For hand held and rig mounted use

**FEATURES**

- Crown > 8mm
- Crown > Solid Crown
- Bonding > Brazed
- Fitting > 1/2" BSP (M)
- Perform > Excellent performance & output

**ALTERNATIVE PRODUCTS**



**DUWC-CROWN**

ORDER LINE: 01909 552470  
 EMAIL: INFO@DURO-YOKOTA.CO.UK

WWW.DURO-DIAMONDS.COM

ACCESSORIES &  
 PROCESS DIAGRAMS





## WET CORE DRILLING OF HEAVY DUTY & REINFORCED CONCRETE APPLICATIONS HAND HELD OR RIG MOUNTED EXTERNAL, NO REQUIREMENT FOR DUST FREE DRILLING

### REINFORCED CONCRETE

All types of brick including class A & B engineering - All types of concrete including light & heavily reinforced Stone such as Hard York - Occasional use in lightweight block and abrasive stone

CORE DRILL OPTIONS

**DUWC**  
CROWN  
ULTRA

Diameters - 18 - 47mm  
Lengths - 350mm



**DPWC**  
CROWN  
PLUS

10 - 32 mm  
200/ 350 mm

**DUWC**  
SEGMENTED  
ULTRA

52 - 250 mm  
450 mm



**DPWC**  
SEGMENTED  
PLUS

35 - 500 mm  
350/450 mm

EXTENSIONS

EXT2  
300mm



EXT1  
300mm



DIRECT FIT / ADAPTORS

#### ADDITIONAL CORE ADAPTORS



AD1  
1/2" BSP (M)  
1-1/4" UNC (M)



AD2  
1/2" BSP (F)  
1-1/4" UNC (F)



AD3  
1/2" BSP (M)




AD4  
1/2" BSP (F)



DPS-SDS-1/2F  
SDS PLUS  
1/2" BSP (F)

DIRECT FIT  
TO ALL DRILLS  
OR EXTENSIONS



POWER TOOL

**DMC6P**  
Rig Mounted  
Reinforced Concrete  
Max 162 mm  
Standard Materials  
202 mm



If Using Hand Held  
Reinforced Concrete  
Max 82 mm  
Standard Materials  
202 mm

**DM12**  
Rig Mounted Only  
In All Materials  
Max 350 mm



**HILTI**  
ALL - 1-1/4" UNC (M) TO 1/2" BSP (F)  
DD130 Suitable for Hilti DD100,  
DD120, DD130, DD150 & DD150-BH



DP-DST-13L  
Water Tank

DRILL RIGS

**B13**



150 mm  
Max  
Core  
Dia

**AS200**



202 mm  
Max  
Core  
Dia

**B14**



200 mm  
Max  
Core  
Dia

**GOMM COLLAR MOUNTED**

**B16**



200 mm  
Max  
Core  
Dia

**S350-1M**



350 mm  
Max  
Core  
Dia

**B32**



350 mm  
Max  
Core  
Dia

**S500-1M**



500 mm  
Max  
Core  
Dia

**RIG MOUNTED**