BREAK IT

DURO


LIGHT DUTY HAMMERS
AA-1.3BRH
5KG



TOKU

Type	AA-1.3BRH
Brand	TOKU
Shank size mm	⬣19 x 50
Bore diameter mm	24
Stroke mm	58
Blows p/min	2,800
J/Blow	12.7
Air cons. l/s	7.5
Weight kg	4.5
Inlet thread	PT 3/8"
Hose diameter mm	10
Vibration m/s²	10
Noise level dB(A)	93

Type	A mm	B mm
AA-1.3BRH	300	76



ELV - Daily Exposure Limit Value
EAV - Daily Exposure Action Value

Product Code	Time to reach ELV (hours:minutes)	Time to reach EAV (hours:minutes)
AA-1.3BRH	2.00	0.30

AA-1.3BRH

- Sub 5kg Chipping hammer
- 19 x 50 mm Hex shank
- Compact & lightweight
- User friendly in confined spaces
- D-Grip handle for greater manoeuvrability
- Suitable for concrete removal on machinery
- Fitted with solid steel screw retainer for use with pointed wide cutting chisels



AVAILABLE STEELS



Moil Point / Point
Drop forged of high grade steel, this hammer iron with heat treated work areas is used for demolition work and starting holes in the centre of a concrete slab. The most common of the demolition steels used for general breaking where there is not a requirement to control the line of fracture.

Part No.
19.0x50HX-MP250



Narrow Chisel
Narrow Chisel is used in a similar way to the Moil Point but the line of fracture is controlled along the line of the chisel end. Used on applications where it is important to have a clean edge retained on the work piece being broken.

Part No.
19.0x50HX-NC250



Wide / Bolster Chisel
Wide Chisel is used in a similar way to the Moil Point but the line of fracture is controlled along the line of the chisel end. Used on applications where it is important to have a clean edge retained on the work piece being broken.

Part No.
19.0x50HX-60WC250

REPAIR & SERVICE DEPARTMENT

REPAIR & SERVICE DEPT.

From the DURO Yokota service centre at our Sheffield head office we are able to offer you full service, repair & preventative maintenance.

- FREE no obligation quotations
- 3 month comprehensive warranty on all work carried out
- Fully traceable repair history through our quality management systems
- Only OEM spare parts used
- Complete maintenance advice service

ORDER LINE: 01909 552470
EMAIL: INFO@DURO-YOKOTA.CO.UK
DURO-DIAMONDS.COM