



AIR ANGLE GRINDERS TAG-900QJL VIBRATION CONTROL 9" (230mm)

Vibration Control

Rock Drills With Up To
70% Less Vibration



Toku Rock Drills are fitted with vibration damping handles for less transfer to the user from the breaker steel. Decrease potential health risks to tool operators & massively increase productivity levels. Vibration levels up to 70% less than equivalent standard model gives significant increases in tool use before current EAV & ELV levels are reached.



TAG-900QJL

ACCESSORIES

STANDARD FLANGES & OUTER WHEEL SCREWS



For type	Part number	Description
TAG-900QJL	2700-040-00*	Outer Flange
	2700-041-00*	Outer Wheel Screw

* Supplied as standard

TOOLS FOR MOUNTING



Part number	Description
8081-0022-00-00*	Spanner H41
9610-1010-00-00*	Hex Wrench H10

RED ROOSTER ATLUB OIL - 1L

All Toku Industrial grinders should be oiled regularly with ATLUB oil. This will significantly increased the lifetime of the air motor and reduces future service costs.



Part Number	ATLUB
-------------	-------

REPAIR & SERVICE DEPARTMENT

From the DURO service centre at our Sheffield head office we are able to offer you full service, repair & preventative maintenance.




- FREE no obligation quotations
- 3 month comprehensive warranty on all work carried out
- Fully traceable repair history through our quality management systems
- Only OEM spare parts used
- Complete maintenance advice service

- 9" - 230 mm Angle grinder
- 6,500 rpm
- Toku designed threaded bolt and flange system to secure cut off / grinding wheel
- Compact & lightweight design
- Two-handed operation
- Handle can be housed on both sides
- For cutting, grinding & sanding applications
- Suitable for industrial applications
- Vibration damping side handle
- Silenced exhaust for increased operator comfort

TECHNICAL DATA

Type	A mm	B mm	C mm	D mm
TAG-900QJL	307	103	36	62



Type	TAG-900QJL
Brand	TOKU
Wheel size mm	230x6.0*x22.23
RPM	6,500
Power kW	1.10
Spindle (Whitworth mm)	N/A
Air cons. l/s	16.6
Weight kg	3.10
Inlet thread	PT 3/8"
Hose diameter mm	13.0
Vibration m/s ²	3.6
Noise level dB(A)	82

* Maximum wheel thickness

ELV - Daily Exposure Limit Value
EAV - Daily Exposure Action Value

Product Code	Time to reach ELV (hours:minutes)	Time to reach EAV (hours:minutes)
TAG-900QJL	15.26	3.51

ALTERNATIVE PRODUCTS



TAG-45MLH



TAG-50MLH

ORDER LINE: 01909 552470

EMAIL: INFO@DURO-YOKOTA.CO.UK

WWW.DURO-DIAMONDS.COM