GRIND IT

DURO

FLOOR GRINDERS
TCG500
DUAL ROTATING DISCS
ELECTRIC & PETROL OPTIONS

DURO·ECO



TRELAWNY

vibration control

ANTI-VIBRATION MOUNTINGS FOR MAXIMUM OPERATOR COMFORT

DUST EXTRACTION

FLOATING SKIRT FOR EFFICIENT DUST CONTAINMENT



TCG500

Type	TCG500-PETROL	TCG500-110V
Weight kg	150	114
Cutting Width mm	590	590
Disc RPM	360	360
Power source	Petrol	110v
Engine type	Honda GXV 160	-
Disc plate size mm	2 x 250	2 x 250
Width / height mm	660/914	660/914
Output power	5.5HP - 4.1 kW	3HP - 2.2 kW
Transformer	-	5Kva
Vibration m/s²	6.3	2.36
Noise level dB(A)	91	86

- Workhorse of choice for contractors looking for a reliable, productive floor grinder
- Suitable for medium to large jobs
- Dual counter-rotating grinding heads ensure balanced operation - 590 mm cutting width
- Safety dead mans switch fitted as standard
- Vibration damping
- Flexible disc coupling ensures maximum contact
- Safety cold start (petrol machines only)
- Special integrated rubberised weight plate system
- 50 mm dust extraction ready
- Levelling and smoothing of concrete
- Removal of coatings and adhesives
- Preparation for new coatings
- Repairing rain-damaged concrete
- Polishing of concrete and other materials
- Requires 5 Kva Transformer

ELV - Daily Exposure Limit Value EAV - Daily Exposure Action Value		
Product Code	Time to reach ELV (hours:minutes)	Time to reach EAV (hours:minutes)
TCG500 Petrol	20.49	5.12
TCG500 110V	24.00	19.32



ACCESSORIES

Floor Grinding Plates to order 8, 10, 16 & 20 segment options available

REPAIR & SERVICE DEPARTMENT

REPAIR & SERVICE DEPT.

From the DURO Yokota service centre at our Sheffield head office we are able to offer you full service, repair & preventative maintenance.

- FREE no obligation quotations
- 3 month comprehensive warranty on all work carried out
- Fully traceable repair history through our quality management systems
- Only OEM spare parts used
- Complete maintenance advice service

ORDER LINE: 01909 552470
EMAIL: INFO@DURO-YOKOTA.CO.UK
DURO-DIAMONDS.COM