




## MI-20P

### INDUSTRIAL

- 1,000Nm Maximum torque output
- 3/4" Square drive
- Suitable for industrial & vehicle maintenance applications
- Compact & lightweight
- Twin hammer impact mechanism
- 4 Level power adjustment
- Ergonomic & well balanced design
- Exhausts through handle with integrated silencer for increased operator comfort
- Vibration level 4.6m/s<sup>2</sup>

Type	MI-20P
Brand	TOKU
Square drive	3/4"
Type	Ring & Hole type
Bolt capacity mm	24
Impact mechanism	Twin-Hammer
RPM	5,000
Torque Nm	1,000
Power adjustment	R/L 4 levels
Air cons. l/s	9.6
Weight kg	3.9
Inlet thread	PT 3/8"
Hose diameter mm	10
Vibration m/s <sup>2</sup>	4.6
Noise level dB(A)	92

### IMPACT MECHANISMS



The twin-hammer system makes 2 impacts per rotation at both sides of the anvil. Same principal as the 2-hammer system, manufactured differently.


ELV - Daily Exposure Limit Value

EAV - Daily Exposure Action Value

Product Code	Time to reach ELV (hours:minutes)	Time to reach EAV (hours:minutes)
MI-20P	9.27	0.22

### TECHNICAL DATA

Type	A mm	A* mm	B mm
MI-20P	215		38



## REPAIR & SERVICE DEPARTMENT

From the Yokota UK service centre at our Sheffield head office we are able to offer you full service, repair & preventative maintenance.

- FREE no obligation quotations
- 3 month comprehensive warranty on all work carried out
- Fully traceable repair history through our quality management systems
- Only OEM spare parts used
- Complete maintenance advice service